



Model 83-RP

High Pressure Relief Pilot

Specifications:

The pilot shall be Singer Model 83-RP, with the spring range specified.

- The normally closed pilot shall be of brass and bronze construction with a spring to adjust the opening pressure.
- The pilot and inner valve shall be of stainless steel 316 construction and the inner valve shall have EPDM resilient compound for seating. The EPDM compound must be bonded permanently to the inner valve and be ground flat and square to assure maximum performance.
- The pilot shall be self-cleaning by locating the inlet directly into the seat area through the bottom of the pilot and the outlet ninety degrees to the inlet.
- A separate port will sense pressure either upstream or downstream (subject to application) to open the pilot and therefore the main valve when system pressure exceeds the pilot set point.
- Maximum Working Temperature: 180 degree F (82 degree C)
- Maximum Working Pressure: 600 psi (42 bar)
- Spring Ranges: Standard 200 to 500 psi (13.78 to 34.5 bar)

Approximate PSI per Turn
80 PSI (5.5 bar) per Turn

Singer Valve Inc.

12850 - 87th Avenue • Surrey, British Columbia, Canada V3W 3H9
Tel: 604 594 5404 • Fax: 604 594 8845 • Toll-Free Fax (US & Canada): 1 800 663 7266
E-Mail: singer@singervalve.com • singervalve.com
An ISO 9001:2000 Registered Company