

SINGLE POINT INSERTION FLOW METERING VALVE

Model 106-SPI-MV







With over 100 years of combined waterworks experience, we have teamed up with McCrometer to provide a unique solution for invalve flow measurement. Using McCrometer's proven Single Insertion Meter technology along with the reliability of a Singer[®] valve, it allows users to have both a flow meter solution along with any function of control valve. Whether it is pressure reducing, level control, or sustaining - all can be installed now with a very accurate flow meter solution.

By adding dual solenoid control to the pilot system and utilizing the Singer MCP Multi Channel PLC Controller, we now have a fully automated control system able to control to any input required and all able to function within your existing SCADA system.

UNPRECEDENTED ENGINEERING DESIGN

The Singer® Model 106-SPI-MV is a Single Point Insertion Electromagnetic Flow Meter, installed and calibrated in conjunction with a Singer valve to provide an accurate flow rate that can be utilized with the metering valve as a stand alone option or built into a 106-2SC-PCO pilot system to provide complete flow-based valve control.

The compact insertion design fits in confined spaces and offers complete accessibility. The flow meter can be removed for easy inspection, cleaning, calibrating or verification.

This cost effective flow meter option is available for valve sizes from 3" (80mm) to 36" (900mm) inches. The flow sensor comes precalibrated from McCrometer's NIST traceable Calibration Lab and requires no recalibration in the field. With no moving parts and a single-piece design, the SPI Mag's sensor contains nothing to wear or break, and it is generally immune to clogging by sand, grit or other debris.

The 106-SPI-MV Mag is profiled for the valve body, further enhancing its measurement accuracy by allowing precise determination of mean velocities.

Section 24 McCrometer

KEY FEATURES

- Accurate flow metering, combined with control valve to save space / cost
- Supplied with Flow Converter for local display with 4-20mA output measurement or can be combined with PLC-based control panel for flow control applications
- +/- 2% of rate accuracy, NIST traceable



Single Point Insertion Flow Metering Valve

SINGLE POINT INSERTION FLOW METERING VALVE

This cost effective flow meter option is available for valve sizes from 3" (80mm) to 36" (900mm) inches. The flow sensor comes pre-calibrated from McCrometer's NIST traceable Calibration Lab and requires no recalibration in the field.

Single Point Insertion Flow Metering Valve

MEASUREMENT

Volumetric flow in valves 3" (80mm) to 36" (900mm) diameter utilizing insertable velocity sensor. Flow indication in English Standard or Metric units.

Flow Measurement Method: Electromagnetic

Accuracy: ±2% of reading

Velocity Range: +0.3 to +32 ft/s (+0.09 to +10 m/s) Has reverse flow indication.

Conductivity: Minimum conductivity of 5µS/cm

DIMENSIONS





VALVE SIZE	A	В	C	D	E
3″ (80mm)	0.38″ (10mm)	7.64″ (193mm)	1.3″ (33mm)	8″ (203mm)	4″ (102mm)
4″ (100mm)	0.5″ (12.5mm)	7.5″ (191mm)	1.8″ (45.7mm)	8″ (203mm)	4.7″ (119mm)
6″ (150mm)	0.75″ (18.8mm)	7.25″ (184mm)	2.4″ (61mm)	8″ (203mm)	6.1″ (155mm)
8″ (200mm)	1″ (25mm)	7″ (178mm)	2.5″ (63.5mm)	8″ (203mm)	7.5″ (191mm)
10″ (250mm)	1.25″ (31.3mm)	6.75″ (172mm)	3.6″ (91.4mm)	8″ (203mm)	8.4″ (213mm)
12″ (300mm)	1.5″ (37.5mm)	6.5″ (166mm)	4.5″ (114mm)	8″ (203mm)	10.5″ (267mm)
16″ (400mm)	2″ (50mm)	6″ (153mm)	5″ (127mm)	8″ (203mm)	11.8″ (300mm)
20″ (500mm)	2.5″ (62.5mm)	7.5″ (192mm)	5.5″ (140mm)	10″ (254mm)	14.4″ (366mm)
24″ (600mm)	3″ (75mm)	7″ (179mm)	5.5″ (140mm)	10″ (254mm)	17.1″ (434mm)
28″ (700mm)	3.5″ (87.5mm)	6.5″ (167mm)	6.5″ (165mm)	10″ (254mm)	18.6″ (472mm)
36″ (750mm)	4.5″ (93.8mm)	7.5″ (211mm)	8.5″ (215mm)	12″ (305mm)	25.5″ (648mm)



SPI PROBE ENVIRONMENTAL RATING

IP 68 Submersible Sensor Up to 160°F (71°C) at 250 PSI (17.2 bar)

MATERIALS

Sensor Head: Polyurethane

Probe Pipe Sleeve: 316 Stainless Steel Pipe

Electrodes: 580 Grade Carbon Rod

Nipple: 316 Stainless Steel

Compression Seal Assembly: 316 Stainless Steel

Compression Seal: Buna "N" O-Ring

VALVE SIZE	SENSOR DIA.	TOTAL SENSOR LENGTH				
3″ (80mm)	1″ (25mm)	8″ (203mm)				
4″ (100mm)	1″ (25mm)	8″ (203mm)				
6″ (150mm)	1″ (25mm)	8″ (203mm)				
8″ (200mm)	1″ (25mm)	8″ (203mm)				
10″ (250mm)	1″ (25mm)	8″ (203mm)				
12″ (300mm)	1″ (25mm)	8″ (203mm)				
16″ (400mm)	1″ (25mm)	8″ (203mm)				
20″ (500mm)	1″ (25mm)	10″ (254mm)				
24″ (600mm)	1″ (25mm)	10″ (254mm)				
28″ (700mm)	1″ (25mm)	10″ (254mm)				
36″ (750mm)	1″ (25mm)	12″ (305mm)				

Single Point Insertion Flow Metering Valve

SPI CONVERTER

OVERVIEW

- CE Certified
- Pre-programmed
- Curve-fitting algorithm to improve accuracy
- Eight line graphical display
- Three key touch programming
- Galvanic separation to 50VDC between analog, pulse / alarm, and earth / ground

DIGITAL OUTPUTS

Four separate digital programmable outputs: open collector transistor usable for pulse, frequency, or alarm settings.

- Volumetric Pulse
- Directional Indication
- Flow Rate (Frequency)
- High / Low Flow Alarms
- Hardware Alarm
- Empty Pipe
- Range Indicator

CHOOSE A CONVERTER FOR YOUR APPLICATION

LOCAL CONVERTER (STANDARD)

- IP67 Die Cast Aluminum
- 6.75" wide x 5.75" high x 6.7" deep (172mm wide x 146mm high x 170mm deep)



ENVIRONMENTAL RATING

 -4° to 140°F (-20°C to +60°C) Operating and storage temperature

POWER REQUIREMENTS

- AC: 90-265V 45-66 Hz (20W/25VA) (Standard)
- DC: 10-35V (21W) (Optional)

DUAL 4-20MA OUTPUTS

• Galvanically isolated and fully programmable for zero and full scale

INSTALLATION DETAILS

- These units can be installed in modulation & non-modulation applications
- These units can be installed with Singer[®] AC (Anti-Cav) cages
- Sensor can be installed on either side of valve-inlet only

PANEL MOUNT CONVERTER (OPTIONAL)

- IP65 Plastic Composite
- 6.5" wide x 3.13" high x 7.25" deep (165mm wide x 80mm high x 184mm deep)



Single Point Insertion Flow Metering Valve

INSTALLATION DETAILS





straight pipe upstream flange to flange from any in-line device, elbow, or tee.

For most application you need 3 pipe diameters Gate valve can be mounted next to Singer[®] valve.



A vertical butterfly valve will need only one pipe diameter to the valve. Horizontal butterfly needs 3 pipe diameters.

106-SPI-MV	FLOW CAPACITY										
Size (inches)	3″	4″	6″	8″	10″	12″	16″	20″	24″	28″	36″
Size (mm)	80 mm	100 mm	150 mm	200 mm	250 mm	300 mm	400 mm	500 mm	600 mm	700 mm	900 mm
Minimum (USGPM) Flat Diaphragm	5	10	20	40	-	-	-	-	-	-	-
Minimum (USGPM) Rolling Diaphragm	-	-	0.5	1	3	3	3	10	10	10	20
Minimum (L/s) Flat Diaphragm	0.3	0.6	-	-	-	-	-	-	-	-	-
Minimum (L/s) Rolling Diaphragm	-	-	0.03	0.06	0.2	0.2	0.2	0.6	0.6	0.6	1.3
Maximum Continuous (USGPM)	460	800	1,800	3,100	4,900	7,000	11,000	17,500	25,000	33,600	55,470
Maximum Continuous (L/s)	29	50	114	196	309	442	694	1,104	1,577	2,120	3,500

1. Usually operating in the continuous "C", service range up to 20 ft/s (6 m/s) - refer to chart and/or performance curves.

2. Ensure the maximum working pressure rating of the valve exceeds the maximum operating pressure

ORDERING REQUIREMENTS

At the time of ordering, please be prepared to provide the following information:

Valve Size

• Pilot Orientation

Converter Type

• Supply Voltage • Cable Length

SCHEMATIC DRAWING

NO.	DESCRIPTION
1	Main Valve
2	SPI Probe
3	SPI Converter
4	Grounding Ring



MODEL 106–SPI–MV Single Point Insertion Flow Metering Valve

MAIN VALVE BODY SPECIFICATIONS

- Valve(s) shall be a hydraulically operated globe valve. The inner valve assembly shall be top and bottom guided by means of easily replaceable bearing bushings. The inner valve assembly shall be the only moving part and shall be securely mounted on a 316 stainless steel stem. The stainless steel stem shall be provided with wrench flats on all valves 3" (75mm) to 8" (200mm), for ease of assembly and maintenance.
- All pressure containing components shall be constructed of ASTM A536-65/45/12 ductile iron. The flanges shall be designed to ANSI Class 150 or Class 300 standards. Flange drilling to ANSI shall be standard however British, ISO and other drillings shall be available upon request.
- Valve(s) shall have a protective fusion bonded epoxy coating internally and externally. The protective fusion bonded epoxy coating shall conform to the ANSI / AWWA C116 / A21.16 (current version) specification.
- 3" (75mm) Valve(s) shall provide smooth "frictionless" motion with actuation being achieved by the use of a flat style EPDM diaphragm. They shall be constructed of nylon fabric bonded with synthetic rubber. The diaphragms shall not be used as a seating surface. No lip seals or packing may be used to seal the actuator.
- Valve(s) 6" (150mm) and larger shall provide smooth "frictionless" motion and maximum low flow stability with actuation being achieved by the use of the Singer® rolling diaphragm technology. The diaphragms shall not be used as a seating surface. No lip seals or packing may be used to seal the actuator.
- The valve cover shall have a separate stem cap giving access to the stem for alignment check, spring installation and ease of assembly.
- On valve(s) 4" (100mm) and larger, bonnets shall be accurately located to bodies utilizing locating pins. Locating pins shall eliminate corrosion resulting from the use of uncoated ductile iron to ductile iron surfaces.
- Valve(s) 4" (100mm) and larger shall have the 316 stainless steel seat, bolted in place, utilizing "Spiralock" thread tapping technology. The 316 stainless steel seat ring shall be easily replaceable without special tools.
- The valve(s) shall form a drip tight seal between the stationary stainless steel seat ring and the resilient disc, which has a rectangular cross-section and is retained by clamping on three and one half sides. The resilient disc shall be constructed of Buna or EPDM for normal service conditions.
- All external fasteners shall be 18/8 stainless steel with 18/8 washers.
- All repairs and maintenance shall be possible without removing the valve from the line. To facilitate easy removal and replacement of the inner valve assembly and to reduce unnecessary wear on the guide, the stem shall be vertical when the valve is mounted in a horizontal line.
- Each valve shall be tested prior to shipment. The standard test shall include a pressure test and a full functional, operational test when pilots and accessories are fitted to suit a particular application.
- The valve(s) shall be covered by a minimum three year (3) warranty against defects in materials and workmanship. The stainless steel seat ring shall be covered by a lifetime replacement warranty.

Single Point Insertion Flow Metering Valve

MAGNETIC FLOW METER

- The valve shall be installed with a 1" (25mm) Single Point Insertion Magnetic Flow Meter in one of the inlet body tappings.
- Unit will be factory installed and programmed with correlative factors for Main Valve body flow profile.
- The flow meter shall consist of two components: an electromagnetic sensor and a converter.
- The 1" (25mm) electromagnetic sensor shall be capable of operating in valves from 4" (100mm) to 36" (900mm).
- The flow meter shall determine the volumetric flow rate by means of the Continuity Equation where flow rate "Q" equals mean velocity "V" times cross sectional area "A" (Q = V x A). The velocity measurement must be taken at a known location, then, through empirically established equations, the sensed velocity will be converted to a mean velocity.
- The flow meter converter shall be microprocessor based with a keypad for instrument set up and LCD displays for totalized flow, flow rate engineering units and velocity. The converter shall power the flow-sensing element and provide a galvanically isolated Dual 4-20mA output.
- It shall be possible, in the test mode; to easily set the converter outputs to any desired value within the range. The 4-20mA scaling, time constants, pipe size, flow proportional output, engineering units and test mode values shall be easily set via the keypad and display.
- Four separate fully programmable alarm outputs shall be provided to indicate empty pipe, forward / reverse, polarity (normally open / close), analog over-range, fault conditions, high / low flow rates, percentage of range, and pulse cutoff. The converter shall periodically perform self-diagnostics and display any resulting error messages. All set up data and totalizer values may be protected by a password.
- The flow-sensing element shall be of an electromagnetic single point type design and factory calibrated to traceable standards, such as NIST. The sensor shall be made of a polyurethane with pure carbon electrodes exposed to flow.
- To eliminate erroneous readings due to pipe wall effects, the sensor must have its electrodes located at least 3/16" from pipe wall and be designed with a curved tip shape, so as not to collect debris while in the operating position. Flat tipped or Doppler sensors shall not be acceptable.
- The sensor cable is 20 feet (6m) of multi-conductor, abrasive resistant, PVC jacketed submersible cable flexible to -400F/C. The sensor cable shall be permanently bonded to the sensor. Additional sensor cable, up to 200 feet (61m), shall be available as an option.
- The insertion tube and restraining rods assembly shall be provided for the smooth installation and operation of the velocity sensor and shall be of sufficient length to allow a full profile of the flow conduit. The stainless steel insertion tube shall be rated for 250 psi (1,724 Kpa) @ 1600 F (710C).
- Hardware must allow sensor to be secured by bolts when sensor is being inserted and retracted. A stainless steel compression seal assembly shall also be supplied.
- No flow meters with accuracies expressed as a percentage of full scale will be accepted and flow meter must be NIST Traceable.

We will not act for or makes no warranty, either expressed or implied, on behalf of McCrometer. We will warranty main valve as covered in our standard warranty. Items manufactured by McCrometer will be covered under their standard warranty. In no event shall we be liable to anyone for special, collateral, incidental, or consequential damages in connection with or arising out of use of this equipment. We reserve the right to revise and improve its products as it sees fit.

SUBMITTAL NO.



ABOUT US

We design and manufactures automatic control valves for the global water industry. Since 1957, our pilot operated diaphragm control valves have been installed on virtually every continent around the world. Whether it is water loss management in Southeast Asia, water conservation concerns in Saudi Arabia or urban distribution demands in the United States, we provide water management solutions to governments, cities, companies, and contractors around the world.

Many of our innovative products are ones that have been born out of our inherent desire to solve an application challenge. Presented with a problem, our team of electronic, instrumentation and control valve specialists are relentless in their research and design until they find a solution.

We care about performance. That's why our control valves are manufactured to the highest quality so that you have one less thing to worry about.

WHAT OUR CLIENTS SAY

"Singer[®] has a proven history of solid performance and it offers excellent product support. That's why South East Water specified a Singer valve."

Warren Roberts, Mechanical Supervisor Siemens Ltd. Melbourne, Australia

"We have been very pleased with our Singer valves. The product quality and service support have been outstanding."

Steve Fassio, SCADA Technical Support City of Modesto, California, USA

"This was a very complicated, very unusual application, and it was very successful. Singer valve gets a gold star."

Dave Buchwald, Fluid Dynamics Specialist Pipestone Industrial Ltd., Colorado USA

"The Singer valve is working fantastically. It is a simple and efficient solution with minimal maintenance."

Billy Weirich, Utilities Superintendent Pittsfield Township, Michigan USA

SINGER[®] GLOBAL OFFICES



CANADA HEAD OFFICE

Singer Valve Inc. 12850 – 87th Avenue Surrey, BC V3W 3H9 Canada

Tel: 604.594.5404 Fax: 604.594.8845 Toll Free Fax (Canada & USA): 1.800.663.7266 Singer@singervalve.com

USA OFFICE

Mailing Address: Singer Valve LLC PO Box 668588 Charlotte, NC 28266 Shipping Address: 1873 Scott Futrell Drive Charlotte, NC 28208

Tel: 833.367.6835 mark@singervalve.com

UNITED ARAB EMIRATES OFFICE

Singer Valve Middle East FZE PO Box 121326 SAIF Free Zone, Q3 – Unit 94 Sharjah International Airport FREE ZONE Sharjah, UAE

Tel: +971.6.557.8116 Fax: +971.6.557.8117 Canadian@singervalve.com

COLOMBIA OFFICE

Singer Valve Latin America Carrera 45, No. 16 Sur 190 Opalo 1105 – El Poblado Medellin, Colombia

Tel: +57.310.4194165 pegan@singervalve.com

MALAYSIA OFFICE

SVM Water Controls Sdn. Bhd. No 6, Jalan MJ 4, Medan Maju Jaya, Batu 7, Jalan Klang Lama 46200 Petaling Jaya Selangor Darul Ehsan, Malaysia

Tel: 603.7784.4043 / 603.7784.4044 Fax: 603.7781.8312 Svmwc@svm.com.my

CHINA OFFICE

Singer Valve (Taicang) Company Ltd. No.88 East Dalian Road, Taicang, Jiangsu, China

Tel: 86.512.5320.6188 Fax: 86.512.5320.6099 Iijun@singervalve.com



LET US PROVIDE YOU A SOLUTION

Connect with us today.

singervalve.com

Canada | USA | Columbia | UAE | Malaysia | China

For more information about us or to view our full line of water products, please visit www.singervalve.com or call Singer® customer service at 833.367.6835.

Mueller refers to one or more of Mueller Water Products, Inc. a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller[®], Echologics[®], Hydro Gate[®], Hydro-Gate[®], HYMAX[®], Jones[®], Krausz[®], Mi.Net[®], Milliken[®], Pratt[®], Singer[®], and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands and krauszus acom to learn more.

Copyright © 2019 Mueller SV, Ltd. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(§).