STAINLESS STEEL HOSE STAINLESS STEEL BRAIDED HOSE



COPPER

Standard material for tubing Corrosion resistant Reliable and long-term performance



STAINLESS STEEL

Optional upgrade Significantly stronger and more durable Corrosion and oxidation resistant

STAINLESS STEEL BRAIDED HOSE

Optional upgrade Completely flexible Significantly stronger and more durable Corrosion and oxidation resistant • Available with stainless or brass ends

		Size	Working Pressure	Lengths	Connection Type
Copper	Standard	1/4 in / 6 mm 3/8 in / 9.5 mm 1/2 in / 12.7 mm 3/4 in / 19 mm	1/4 in: 1,406 psi / 96.9 bar 3/8 in: 984 psi / 67.8 bar 1/2 in: 727 psi / 50.1 bar 3/4 in: 511 psi / 35.2 bar	Any	SAE
Stainless Steel	Optional Upgrade	1/4 in / 6 mm 3/8 in / 9.5 mm 1/2 in / 12.7 mm 3/4 in / 19 mm	1/4 in: 21,000 psi / 1,447.3 bar 3/8 in: 14,000 psi / 965.5 bar 1/2 in: 10,500 psi / 724.1 bar 3/4 in: 7,000 psi / 482.8 bar	Any	Compression
Braided Hose	Optional Upgrade	1/4 in / 6 mm 3/8 in / 9.5 mm 1/2 in / 12.7 mm 3/4 in / 19 mm	1/4 in: 3,000 psi / 206.8 bar 3/8 in: 2,500 psi / 172.4 bar 1/2 in: 2,000 psi / 137.9 bar 3/4 in: 1,500 psi / 103.4 bar	Any	SAE / JIC

ORDERING INSTRUCTIONS

Refer to page 244 for the order form and ordering instructions.

Additionally, include the following information for this product:

• Material(s)