

MODEL NUMBER:

SINGLE-PROCESS CONTROL PANEL
W/ TOUCH PANEL INTERFACE

SCP - TP - _____ - _____

CATALOG SELECTION:

SCP-TP- XX- XXXXXX

FRONT DOOR
CD - CLEAR DOOR
OD - OPAQUE DOOR

SUPPLY VOLTAGE
120VAC - 120VAC, 60 Hz (Main Supply, Solenoid Supply)
240VAC - 240VAC, 50 Hz (Main Supply, Solenoid Supply)
024VDC - 24VDC (Main Supply, Solenoid Supply)

CONTROL SELECTION CONFIGURATION:

**NOTE: INFORMATION BELOW WILL BE USED FOR FACTORY TO PRESET CONTROL PANEL CONFIGURATION TO ASSIST USER. MISSING INFORMATION WILL NEED TO BE CONFIGURED BY USER AT TIME OF COMMISSIONING

APPLICATION (CHOOSE ONE OF THE FOLLOWING):

- 1 MODULATING SINGLE PROCESS CONTROL
 - VALVE POSITION PRESSURE REDUCING
 - FLOW PRESSURE SUSTAINING
 - MODULATING LEVEL
- 2 ON/OFF CONTROL
 - ON/OFF LEVEL OTHER: _____
- 3 MOTORIZED 4-20mA ACTUATOR CONTROL
 - 420DC OTHER: _____

PROCESS VARIABLE CONFIGURATION

TRANSMITTER RANGE: _____


ALARM/RELAY OUTPUT (CHOOSE TWO OF THE FOLLOWING):

- 1 SENSOR BREAK 5 MODBUS TOGGLE
- 2 MANUAL MODE 6 STRAINER FLUSH
- 3 LOCAL/REMOTE
- 4 POSITIONING ALARM

MODBUS COMMUNICATION (CHOOSE ONE OF THE FOLLOWING):

- 1 SERIAL ENABLE
- 2 ETHERNET ENABLE

FORM FILLED OUT OR EDITED BY:



SCREEN AND KEYPAD
INSTALLED ON AN INTERNAL
DOOR

ENCLOSURE STANDARD SPECIFICATION:

MATERIAL: POLYCARBONATE
ENVIRONMENTAL RATING: NEMA TYPE 4,4X,12,13
IEC 60529, IP66, IP67
DIMENSIONS: 11.81"(300mm) x 11.81"(300mm)
x 7.49" (190mm)

ADDITIONAL NOTES:

This quotation/submittal is for panels(s) described above and reflects our understanding of functions required. We assume no responsibility for meeting all stated or implied requirements beyond functions listed above. If above does not adequately describe functions/operation of above products, please ask for a more comprehensive description and mention areas where above description is deficient.